

PROJECT NAME: _____
LOCATION: _____
SPECIFIER ITEM NO. _____ **QTY:** _____
ENCORE PART NO. _____

Encore® Single Deck Mount Pre-Rinse Assembly with Lever Handle

KL63 Series

Model	Flow Rate	Valves	Spring	Wall Bracket
KL63-1000	1.6 gpm	Compression	Chrome Plated	None
KL63-1100	1.6 gpm	Ceramic	Chrome Plated	None
KL63-10L2	1.2 gpm	Compression	Chrome Plated	None
KL63-11L2	1.2 gpm	Ceramic	Chrome Plated	None
KL63-10L3	.65 gpm	Compression	Chrome Plated	None
KL63-11L3	.65 gpm	Ceramic	Chrome Plated	None
KL63-1000-S	1.6 gpm	Compression	Stainless Steel	None
KL63-1100-S	1.6 gpm	Ceramic	Stainless Steel	None
KL63-10L2-S	1.2 gpm	Compression	Stainless Steel	None
KL63-11L2-S	1.2 gpm	Ceramic	Stainless Steel	None
KL63-10L3-S	.65 gpm	Compression	Stainless Steel	None
KL63-11L3-S	.65 gpm	Ceramic	Stainless Steel	None
KL63-1000-BR	1.6 gpm	Compression	Chrome Plated	Yes
KL63-1100-BR	1.6 gpm	Ceramic	Chrome Plated	Yes
KL63-10L2-BR	1.2 gpm	Compression	Chrome Plated	Yes
KL63-11L2-BR	1.2 gpm	Ceramic	Chrome Plated	Yes
KL63-10L3-BR	.65 gpm	Compression	Chrome Plated	Yes
KL63-11L3-BR	.65 gpm	Ceramic	Chrome Plated	Yes
KL63-1000-BS	1.6 gpm	Compression	Stainless Steel	Yes
KL63-1100-BS	1.6 gpm	Ceramic	Stainless Steel	Yes
KL63-10L2-BS	1.2 gpm	Compression	Stainless Steel	Yes
KL63-11L2-BS	1.2 gpm	Ceramic	Stainless Steel	Yes
KL63-10L3-BS	.65 gpm	Compression	Stainless Steel	Yes
KL63-11L3-BS	.65 gpm	Ceramic	Stainless Steel	Yes

Optional mixing valve – Model KL63-Y005

ADD-ON FAUCETS

Model	Spout Length
KL55-7006	6" (152mm)
KL55-7008	8" (203mm)
KL55-7010	10" (254mm)
KL55-7012	12" (305mm)
KL55-7014	14" (356mm)
KL55-7016	16" (406mm)
KL55-7018*	18" (457mm)
KL55-7018ASE1	18" (457mm)
KL55-7024*	24" (610mm)

*Double-jointed spout

Approximate shipping weight - 10 lbs
Warranty - 3 years parts



Low-Flow Spray Valve

- 1.6gpm Flat Spray standard
- Spray head hook holds spray head away from work area when not in use
- Heat resistant, non-marring, impact resistant bumper will not fatigue under extreme operating temperatures

Encore Premium Hose Feature

- 3-ply nylon reinforced Santoprene® inner hose provides maximum durability
- Interlocking helical coils of stainless steel outer hose shroud protect inner hose
- Patented stainless steel strain relief spring transfers and distributes load stress to significantly improve hose life
- High pressure hydraulic fittings on hose ends tested to 400psi
- Washerless design incorporates temperature resistant O-rings to provide leak-proof seal on all hose assemblies and hose grips

Kool Grip™ Hose Grip

- Reduces heat transfer to the hand; stays up to 30 degrees cooler than competitors' grips
- Ergonomic spray handle fits comfortably in even small hands and is easy to use

COMPLIES WITH:
THE FEDERAL "REDUCTION OF LEAD
IN DRINKING WATER ACT" –
2011 – US SENATE BILL NO. S.3874
NSF/ANSI 61/9, ANNEX G




KL63 Series

Single Deck Mount Pre-Rinse Assembly with Lever Handle

PREMIUM PLUMBING PRODUCTS
Encore®

1890 Swarthmore Avenue, PO Box 2020, Lakewood, NJ 08701
Phone: 800-526-3694, 732-363-4700, Fax: 732-364-8110
www.encoreplumbing.com • www.componenthardware.com



SPECIFICATIONS:

Single Deck Mount Pre-Rinse Assembly to be Encore KL63 Series
Model _____.

Pre-rinse body to be constructed of polished chrome plated brass. Pre-rinse hose to be constructed of 3-ply nylon reinforced Santoprene® permanently secured with high pressure hydraulic fittings pressure tested to 400 psi. Hose to be of washerless, leak-proof design, protected by interlocking helical stainless steel coils for maximum protection and flexibility. Patented stainless steel strain relief spring transfers load stress. Heavy-duty ergonomic gooseneck spring ensures proper hose position. Riser to include spray head hook to hold spray head away from work area when not in use. Spray assembly to be equipped with Kool Grip™ handle to reduce heat transfer to hand.

1-1/4" (32mm) hole for deck is recommended.
1/2" NPT Male Inlets w/ 1/4" NPT Compression Fittings
Operating Temperature: 40-180°F (5-83°C)
Operating Pressure: 15-125psi